

Function 1: System parameters

F11 — Initialization

Important: Before programming, make sure you initialize the system!

F12: Installer

Range: 2–8 digits. Default: 789

F13: Administrator

Range: 2–8 digits. Default: 456

F14 — Time/date

F15 — System timing parameters

F151: Flash hook duration

Range: 2–20 (0.2–2.0 seconds). Default: 15 (1.5 seconds).

F152: Transfer/forward recall timer

Range: 1–9 rings. Default: 3.

F153: Hold/park recall timer

Range: 5–960. Default: 60.

F16 — Recording alert tone

Enable / disable

Default: Disabled

F17— System speed-dial

Use the input sheet on the following page.

F17— System speed dial

Loc.	Name	Number
600		
601		
602		
603		
604		
605		
606		
607		
608		
609		
610		
611		
612		
613		
614		
615		
616		
617		
618		
619		
620		
621		
622		
623		
624		
625		

Use a blank sheet for additional speed dial numbers 626–699.

Function 2: CO lines

F21 — CO line programming

Day

CO	Line Grp.	Ring 1	Ring 3	Ring 5	Ring 9
1					
2					
3					
4					
5					
6					

Night

CO	Line Grp.	Ring 1	Ring 3	Ring 5	Ring 9
1					
2					
3					
4					
5					
6					

F22 — Access codes/toll restriction

F221: Centrex/ PBX access codes

Line Group 9

Default: 0.

--

Line Group 8

Default: 0.

--

Line Group 7

Default: Disabled.

--

F222: Toll restriction exception tables

Allow Numbers: _____

Deny numbers: _____

F23 — CO line parameters

Overview and programming steps begin on page H.5.

F231: Line receive volume

Range: 0–12. Default: 10.

--

F232: Line disconnect

Range: 1–255. Default: 6.

--

F24 — Caller ID

Enable / disable

Default: Disabled

--

Local — 7: _____

Local — 10: _____

Function 3 : Extension programming

F31 — Extension definition and routing

Ext.	Type	Name	LG	CFD	CFN	Pg Zone	Ext.
0		Operator					100
100	Digital						
101	Digital						
102	Digital						
103	Digital						
104	Digital						
105	Digital						
106	Digital						
107	Digital						
108	Digital						
109	Digital						
110	Digital						
111	Digital						
112							
113							

F33 — Department programming

Dept.ext.	Name	Type	CFWD day	CFWD night
290				
Ext. list:				
291				
Ext. list:				
292				
Ext. list:				
293				
Ext. list:				
294				
Ext. list:				
295				
Ext. list:				
296				
Ext. list:				
297				
Ext. list:				
298				
Ext. list:				
299				
Ext. list:				

Dept. types: In Order, All, and UCD.

F35 – Extension button mapping

See programming section for button default based on the system configuration.

Function 5: Voice mail programming

F53 — Guest mailboxes

MB	Name
300	
301	
302	
303	
304	
305	
306	
307	
308	
309	

F55 — Message notification

CO line access

Range: 9,8 or 7. Default: 9.

Dialing pause

Range: 1–12. Default: 1.

Pager interval

Range: 0–20. Default: 6.

Function 6: Recordings

F61 — Re-recordable prompts

Prompt	Type	Default	Re-recorded
ID1 Day	No names matched	<input type="checkbox"/>	<input type="checkbox"/>
ID1 Night	End of message	<input type="checkbox"/>	<input type="checkbox"/>
540	Holiday main greeting	<input type="checkbox"/>	<input type="checkbox"/>

F62 — Record directory names

Extension	Recorded name	Keys
100		
101		
102		
103		
104		
105		
106		
107		
108		
109		
110		
111		
112		
113		

F63 — Message-on hold-programming

F631 — MOH source

Range: 590–593. Default: 592.

F633 — MOH volume

Range: 1–12. Default: 6.
